
## HIDEOUT

## Base Color Waterborne Intense White

- Excellent pigment base for Traction® Skate Floor Systems.
- Quick-leveling, low-foam formula excellent for roller application.
- · Complete hide in 1-2 coats.
- Excellent compatibility with Roll-On®, Traction®, Crimp Coat, and most water based finishes.
- · Low-odor, non-flammable, water-based.
- Easy water clean-up.
- High-gloss finish.



DIRECTIONS: Refer to Hideout  $^{\text{TM}}$  brochure for complete preparations and application instructions.

Although thorough screening may be sufficient, an approved primer or laminate coating should be applied to previously coated surfaces. We recommend Crimp Coat™ Laminating Primer.

- For newly installed floors, follow manufactures recommendations for approved primers and sealers before application.
- Application by roller or airless sprayer is recommended.
  For rolling instructions, see Hideout brochure for details and procedures.
- 3. Coverage averages 800 square feet per gallon.
- 4. One hour dry time, recoat in two hours.
- 5. After 4 hours drying, sanding or light screening recommended
- Apply Circles and Lines using recommended acrylic latex enamels.
- 7.Clean up with soap and water.
- 8. Protect from freezing.

## **Properties**

Density - 10.2 lbs/gal

Viscosity - 2000 - 4000 cP (Brookfield)

Solids - 44 - 46%

TiO2 - 17%

Coverage - 600 sq. ft./gal

Dry Time - 1 hour

Recoat Time - 2 hours

VOC - 150 g/L

Meets Strict Clean Air Requirements: VOC (minus

water) < 340 grams/liter.

Classification: Architectural Floor Coating.

Thinning Instructions: Do not thin.

Meets Strict Clean Air Requirements: VOC (minus water) < 340 grams/liter. Classification: Industrial Maintenance Coating. Thinning Instructions: Do not thin.



Roll-On® Floor Systems, LLC 233 WEST PIPELINE ROAD HURST, TEXAS 76053 Phone 817-571-2438 www.roll-on.com